

Snell 1771 Machine Tape



Product Codes : 1237048CL 1237048T

Product Description:

Industrial sealing tape used for carton sealing, splicing and other packaging applications. High tensile strength and good moisture resistance. Ideal for sealing lightweight packages exposed to high distribution hazards or medium to heavy weight boxes exposed to minimal distribution hazards. Conformable polypropylene (BOPP) with synthetic rubber (hot melt) adhesive.

Size & Colour:

1237048CL: 48mm x 100m Clear

1237048T: 48mm x 100m Tan

Features:

Adheres instantly to a variety of surfaces.

Edge tear and split resistance.

Good adhesion to fiberboard.

Roll to roll consistency increases productivity for improved unit costs.

Meets FDA requirements for indirect food contact.

Construction:

Film:	Polypropylene (BOPP)		
Adhesive:	Synthetic Rubber (hot melt), pressure sensitive adhesive		
Film Thickness:	28mu		
Adhesive Thickness:	15mu		
Total Thickness:	43mu		

Physical Properties:

Adhesive to Steel:	45 oz/inch	(Testing Method: ASTM D 3330)
Tensile (Machine Direction):	22lbs./inch	(Testing Method: ASTM D 3759)
Tensile (Cross Direction):	44lbs./inch	(Testing Method: ASTM D 3759)
Holding Power:	3500 min plus	(Testing Method: ASTM D 3654)
Peel Adhesion 180°:	1180g/inch	(Testing Method: ASTM D 3330)

Storage Conditions:

Store in a clean, dry place in moderate temperatures.

Shelf Life:

To obtain best performance, use this product within 18 months of manufacture.

Safety / Environmental Information:

MSDS Class:	S	Hazard Ratings:
Health:	1	Minimal
Fire:	0	Slight
Reactivity:	0	Moderate
VOC:	N/A	Serious
CONEG:	Complies	Extreme

Does not contain any substances according to the Ozone Depleting Substances, 40CFR Part 82 and the Safe Drinking Water and Toxic Enforcement Act of 1986.

Packing:

1237048CL:	48mm x 100m	36 rolls per carton	3024 rolls per pallet
1237048T:	48mm x 100m	36 rolls per carton	3024 rolls per pallet