

## IPNZ PRODUCT RANGE

IPNZ Item	IPNZ Description	
EBH0045	IPEX Hand 500mm x 375M x 20um UV Blown Stretch Film	

Properties				
Measurement	Unit	Target	Test Method	
Colour		Natural		
Gauge	um	20 (+/- 2um)	Thickness Gauge	
Film Width	mm	500 (+/-3mm)	Measuring Tape	
Roll Length	M	375		
Roll Weight	kg	3.45 (+/- 3%)	Electronic Scale	
Core size ID	mm	51		
Pallets		Plain 1200 x 1000mm – Two Way		
Rolls per pallet		160		
Storage		Before film is used it should be kept out of direct natural light/sunlight and in a well-ventilated area at a cool ambient temperature.		
Product Stewardship and Recyclability		Industrial plastics waste companies and recyclers can collect this material for recycling where enough clean PE film is available.  Cardboard cores can be recycled by industrial recyclers if the film and tape is removed.  Cardboard layer pads and wrapping used as packaging on the pallet can be recycled using industrial recyclers.		
Food Contact		The materials used to manufacture this item comply with U.S. FDA Title 21 Code of Regulations Parts 170 – 199 and EU – Commission Regulation No 10/2011.  This film is intended for use as secondary and tertiary packaging material not in direct food contact.		
UV Statement		This film is UV stabilised for outdoor exposure. Film will last up to two years under New Zealand UV exposure		

This technical data sheet and the information contained therein are the property of Integrated Packaging and are disclosed to the specified Customer in confidence. This document must not be copied or otherwise disclosed to any other person or corporation without written permission from Integrated Packaging. The Information tabled are nominal values and do not constitute as a specification.

Review Date: 30 May 2023