

## DESCRIPTION

Inseal 3507 is closed cell PVC foam with a paper release liner on the non-adhesive face. 3507 is coated on one side with a high-quality pressure sensitive acrylic adhesive. 3507 will act as a water seal when it is compressed. Inseal 3507 is available in grey

## APPLICATIONS

- Anti-vibration pads
- Cushioning in cabinet doors
- Cushioning / anti-abrasion in safety shoes
- Suitable for heavy duty applications

## BENEFITS

- Designed for high load bearing applications
- Fire rated to DIN 4102 part 1, B2
- Ultra violet (UV light resistant)
- No known hazards associated with this product

## PRODUCT APPLICATIONS

By hand direct roll applying even pressure. Surface must be clean, dry and free from grease and dirt.

Low temperatures may increase risk of condensation, reducing the tack of the product, and the life expectancy of the product will vary with the temperature and humidity.

Customers are recommended to make their own assessment of our products under their own conditions, for their own requirements.



## SPECIFICATIONS

SHORE HARDNESS "00" SCALE	55
COMPRESSION TO EFFECT SEAL	30% Minimum
FORCE TO COMPRESS BY 30%	7.2 N/cm <sup>2</sup>
COMPRESSION DEFLECTION	6.1 N/cm <sup>2</sup>
UV RESISTANCE	Good
SERVICE TEMPERATURE	-30°C to +70°C
ADHESIVE	Acrylic
THICKNESSES	0.8, 1.5, 3, 4.5, 6mm

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Please refer to the Conditions of Sale for further information.

The conditions under which this product is stored affect its performance. Storage should be in dry, well ventilated rooms with a reasonably consistent temperature around 20°C and protected from continuous exposure to direct sunlight. The product should always be applied to clean, dry and grease free surfaces.