3M Scotch Paper Packaging Tape227

Product Informat	tion	June 200
Description	3M Scotch 227 Paper Packaging Tape is a premium paper packaging tape. It is ideal for carton closure applications and as a craft tape.	
Features	 Specially treated parameters and abrasion resistant 	e gives good holding power on a variety of surfaces per backing provides medium to high tensile strength nce
Physical Properties/T	ypical Performance Cha	racteristics*
	Backing	100 micron flat kraft paper saturated with synthetic based material
	Adhesive	Very aggressive rubber resin adhesive
	Colour	Tan
	Total Thickness	0.18 mm
	Adhesion to steel	63 N/100 mm
	Tensile strength	653 N/100 mm
	Elongation at break	3%
	Temperature range	-30°C to 90°C
	*Not recommended for spo	ecification purposes
Stocked roll sizes	18 mm, 24 mm, 30 mm, 36 mm, 48 mm, 60 mm, 72 mm x 55 m.	
Application ideas	 Carton closure Sealing packaging Picture framing Repairing damaged paper backing Splicing and roll closing of paper and board rolls 	
Shelf life	Store in a dry location out of direct sunlight and away from all sources of heat. Ideal conditions are 20°C and 50% relative humidity. Storage in roll form for more than 12 months in not recommended.	
Further information	Further information is available by contacting 3M Customer Services on Free Phone 0800 200 713 or Free Fax 0800 508 980 or your 3M representative.	
Note	The user is responsible for and method of assembly are	determining whether the 3M product, surface preparation, e suitable for their particular purpose. Failure to determine involved in the application may result in bond failure.

3M

3M New Zealand Ltd Industrial Tape & Adhesives

PO Box 33-246 Takapuna 1332 Phone: 0800 200 713

Fax: 0800 508 980 Email: 3mnz9013@mmm.com

www.3M.com/nz/