

3M™ Peltor™ X Series Headband Earmuffs

Technical Data Sheet



Product Description

Historically higher attenuating earmuffs meant larger and bulky cups, but no longer. The 3M™ PELTOR™ Earmuffs X4 can attenuate by as much as 31dB whilst maintaining a sleek, low profile aesthetically pleasing design.

Using the same innovative technology, the 3M™ PELTOR™ X5 remains relatively lightweight with excellent balance and wearer comfort despite the larger cups, providing ratings as high as SLC80 35dB.

Applications

The 3M™ Peltor™ X Series earmuffs are ideal for protection against noise arising from a wide range of applications in the workplace and leisure activity. Examples of typical applications include airports, construction, manufacturing as well as mining and utilities.

Features

- Modern, attractive low-profile design
- Lightweight
- Testable with the 3M™ E-A-Rfit™ Validation System
- Twin headband design for outstanding balance and comfort
- Electrically-insulated wire headband (dielectric)
- Soft wide cushions help maintain a comfortable pressure around the ears
- Innovative foam earcup inserts and spacers that help improve attenuation
- New ear cushion foam technology for an effective acoustic seal and reliable protection
- Easy-to-replace cushions and inserts help keep them clean
- Hard hat-attached version fits directly to many hard hats without an adapter

Standards

The X4 series earmuffs were tested in accordance with AS/NZS 1270:2002 and met the requirements of hearing protectors.

The product has been tested by an accredited laboratory in accordance with the requirements in AS/NZS 1270.



X4A Headband



X5A Headband

Specifications

Headband and headband cover/sleeve	Stainless steel wire, TPE, Polyester, Polypropylene, Acetal
Earcups ABS/TPU	Earcups ABS/TPU
Earcup Inserts PU Foam	Earcup Inserts PU Foam
Earcup Cushions and Cushion Covers	PU Foam and PVC

Fitting Instructions

- Remove hair or any obstruction from underneath the cushion.
- If spectacles are worn, cushions must be soft and subtle to ensure seal. If safety spectacles are worn in combination a thin side arm spectacle is preferable.

Storage

- Store in an area free of contamination.
- Do not leave your hearing protection device in areas or locations where it can be exposed to damage or contamination.
- Sunlight is particularly damaging as UV light can have a detrimental effect on the materials used in the product.
- Chemical contamination can also have a serious effect on product integrity and decontamination after use is recommended.
- If the product is to be disposed of, it should be disassembled and disposed of as solid waste. Please see local authority

3M™ Peltor™ 3M™ Peltor™ X Series Headband Earmuffs

Laboratory Attenuation Tables

X4A Headband Earmuffs

Class 5	SLC80 31dB						
Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	18.3	19.2	28.1	39.2	38.1	43.7	43.1
Standard Deviation (dB)	5.1	2.9	3.7	4.8	3.1	4.8	5.2
Mean minus Standard Deviation (dB)	13.2	16.3	24.4	34.4	35.0	38.9	37.9

X5A Headband Earmuffs

Class 5	SLC80 35dB						
Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	23.2	25.3	35.8	43.8	39.7	41.5	40.7
Standard Deviation (dB)	4.0	3.4	4.5	3.0	3.8	3.5	3.9
Mean minus Standard Deviation (dB)	19.2	21.9	31.3	40.8	35.9	38.0	36.8

Fitting Instructions

Performance will be reduced by anything that impairs the seal of the cushions against the head eg. thick spectacle frames, balaclavas, etc.

The reported attenuation (noise reduction) will only be obtained if the earmuffs are in good working order and worn as directed.

Storage

Hearing protectors should be inspected prior to use for damage or deterioration. Damaged or worn parts should be replaced prior to use.

Regular cleaning using warm water and soap. Components should be dried prior to use. Mild detergent and hygiene wipes can be used on this product, however some products may harden or damage the cushion.

Hygiene kit/cushions should be replaced when the cushion show signs of damage or hardening.

Ordering Information

Model	Description	3M ID
X4A	Headband Earmuffs X Series Light Green	XA007707947
X5A	Headband Earmuffs X Series Black/Gray	UU008197848
HYX4	Replacement Hygiene Kit for X4 Earmuff	XA007707608
HYX5	Replacement Hygiene Kit for X5 Earmuff	XA007707616
393-3005-2	X4/X5 EARfit Probed Test Cushions	70071691136



3M Australia Pty Ltd
Personal Safety Division
 Bldg A, 1 Rivett Road
 North Ryde NSW 2113
 TechAssist Helpline: 1800 024 464
 Customer Service: 1300 363 565
 Email: techassist@mmm.com
 Web: www.3M.com/au/ppesafety

3M New Zealand Ltd
Personal Safety Division
 94 Apollo Drive, Rosedale
 Auckland 0632
 TechAssist Helpline: 0800 364 357
 Customer Service: 0800 252 627
 Email: techassist@mmm.com
 Web: www.3M.com/nz/ppesafety

WARNING! Hearing Protection Products*
 These hearing protectors help reduce exposure to hazardous noise and other loud sounds. Misuse or failure to wear hearing protectors at all times that you are exposed to noise may result in hearing loss or injury. For proper use, see supervisor, User instructions, or call 3M TechAssist Helpline 1800 024 464.