

3M™ Versaflo™ TR-300+ Filters

Technical Data Sheet

Description

The following filters are made to be used with the Versaflo™ TR-300+ Powered Air Purifying Respirator (PAPR) for protection against particulates and some nuisance concentration gases and vapours. These filters used with the TR-302E+ Powered Air Turbo are part of a respirator system compliant with the Australian/New Zealand Standard AS/NZS 1716:2012

Application

These filters are designed to capture airborne particulates (thermally and/or mechanically generated particulates) of all sizes.

The TR-3802E and TR-3822E also have a limited capability to adsorb organic vapours (TR-3802E) or acid gas (TR-3822E). These are for use against nuisance levels of these gas/vapours ie airborne concentrations that are below the relevant Workplace Exposure Standard (WES) for the specific gas/vapours involved.

For exposures above the WES of gas/vapours, the Versaflo™ TR-600 and its associated filters should be considered.

Protection Factors

When fitted with any of the PAPR-P3 filters, the Versaflo™ TR-300+ PAPR will give the wearer a protection factor of 50 against mechanically and thermally generated particles (AS/NZS 1715).

These PAPR products are available with a range of different headtops for various applications e.g. lightweight head coverings, hoods and headtops.

Specifications

Filtration	>99.95% efficient (AS/NZS1716:2012)
Length	350 (mm)
Width	195 (mm)
Height	125 (mm)
Weight	1.30 (kg)
Expiry	5 years from Date of Manufacture – indicated on filter



Compatible with



TR-300+



QR-TR300PLUS

Scan or Click for
Tech Data Sheet



TR-3712E
PAPR-P3



TR-3802E
PAPR-P3 with nuisance* OV



TR-3822E
PAPR-P3 with nuisance* AG



TR-371+



TR-3600



TR-362E

* Nuisance levels are those levels below the Workplace Exposure Standards/ (WES) Workplace Exposure Limits (WEL)

Service Life

The service life of these filters will vary according to the time of use, the selected flow rate and level of exposure to airborne particulates. There is a visual and audible alarm on the control panel of the air filter unit and an indication of current condition of the particle filter. When the filter is full a warning will sound and the filter will need to be replaced with a new one.

Disposal

If disposal of parts is required, this should be undertaken in accordance with local health and safety and environmental regulations.

Storage

This product should be stored in the packaging provided in dry, clean conditions, away from direct sunlight, sources of high temperature, petrol and solvent vapours. Do not store outside the temperature range -30°C to +50°C or with humidity above 90%. If the product will be stored for an extended period of time before use, the suggested storage temperature is 4°C to 38°C. Before initial use, always check that the product is within the stated shelf life (use by date).

Before selecting a filter the following should be considered:

- Complete a risk assessment.
- Identify and measure the hazardous substances in the workplace environment.
- Compare those airborne contaminants to the relevant workplace exposure limit values.
- When selecting the correct RPE consider the properties of the hazardous substances, the needs and work of the wearer and workplace conditions.
- Does the atmosphere contain sufficient oxygen throughout the period of exposure?
- If there is insufficient oxygen or the contaminant concentrations are unknown or higher than the exposure limits then SCBA or Airline must be used.
- Responsibility for correct filter selection remains with the end user.

Product

The following filter options are available for the TR-302E+ Powered Air Turbo's:

SAP ID	Legacy ID	Availability		Model #	Description
		AUS	NZ		
7100266123	UU011647516	•	•	TR-3712E	3M™ Versaflo™ Filter PAPR-P3, TR-3712E
7100018809	78815069386	•	•	TR-3802E	3M™ Versaflo™ Filter PAPR-P3 with Nuisance O/V, TR-3802E
7100018861	78815069394	•	•	TR-3822E	3M™ Versaflo™ P/HF/Nuisance Level Acid Gas Filter TR-3822E, for 3M™ Versaflo™ TR-300 Turbo Series, 1 Filter/Car, 5 Car/Case
7000059880	AT010592650 (AU) CR180811422 (NZ)	•	•	TR-3600	3M™ Versaflo™ TR-300+ Prefilter, TR-3600, 1/case
7100099577	UU006386765	•	•	TR-371+	3M™ Versaflo™ Filter Cover TR-371+, for TR-300/TR-300+, 1 Bag/Case
7000103970	XA007706659	•	•	TR-362E	3M™ Versaflo™ Spark Arrestor TR-362E, 1/Car, 1 Carton/Case

Limitations of use

- Do not use for respiratory protection against unknown atmospheric contaminants or when concentrations of contaminants are unknown or immediately dangerous to life or health (IDLH).
- Do not use in atmospheres containing less than 19.5% oxygen. (3M definition. Individual countries may apply their own limits on oxygen deficiency. Seek advice if in doubt).
- Do not use against contaminants with poor warning properties.
- The filter cannot be cleaned and should be replaced if excessively dirty.
- Keep inner filter seal clean. The seal can be cleaned with fresh water but ensure that water does not enter the filter.
- Never attempt to clean filters by knocking or blowing out accumulated material.

Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.

SCAN OR CLICK FOR:



PAPR Catalogue
Section



Full Personal
Safety Division
Catalogue

Technical Statement

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards. Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.



3M Australia Pty Ltd
Personal Safety Division
Bldg A, 1 Rivett Road
North Ryde NSW 2113
Customer Service: 1300 363 565
Email: 3msupport.safety.au@mmm.com
Web: www.3M.com/au/ppesafety

3M New Zealand Ltd
Personal Safety Division
94 Apollo Drive, Rosedale
Auckland 0632
Customer Service: 0800 252 627
Email: 3msupport.safety.nz@mmm.com
Web: www.3M.com/nz/ppesafety

3M & Versaflo are trademarks of 3M Company.
© 3M 2025. All rights reserved.