



# Packaging Tape

## Premium Vinyl - Heavy Duty

### TECHNICAL DATA SHEET

## Key Features



Low noise when unwinding, good elongation, and low stretch qualities.



Good puncture resistant properties.



Extra strong carton closure tape.



Suitable for freezer conditions at - 20°C (once applied correctly).



Suitable for use on most recycled cartons (testing is always recommended).



Easy to write on the surface with marker pens.



## Description

**Sellotape® Packaging Tape** is an extra strength premium packaging tape. Suitable for most recycled cartons. Low noise and puncture resistant tape that can be easily written on. Vinyl backing film with natural rubber adhesive

### Available Sizes:

24, 36 & 48mm (width) x 55m (length)

48mm (width) x 100m (length)

SKU: 2006300, 2006729, 2006332, 908897



MANUFACTURED IN ITALY

## TECHNICAL INFORMATION

Backing	UPVC - Unplasticised polyvinyl chloride
Adhesive	Natural Rubber
Colour	Brown
Thickness	52 microns PSTC 133
Total thickness tolerance: + or - 2 microns	
Tensile Strength	125N / 25mm PSTC 131
Elongation at break	60% PSTC 131
Adhesion to steel	3.2N / 25mm PSTC 101
Service Temperature	0°C to 60°C
Storage Temperature	10°C to 25°C
Shelf life	12 months from manufacture date.



## Applications

- Ideal for carton closure, bundling of rods, tubes, pipes and general securing.
- For light/ medium weight carton closure.

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification.

Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Please refer to the Conditions of Sale for further information.

The conditions under which this product is stored affect its performance. Storage should be in dry, well ventilated rooms with a reasonably consistent temperature around 20°C and protected from continuous exposure to direct sunlight. The product should always be applied to clean, dry and grease free surfaces.