



TECHNICAL DATA SHEET

General purpose Masking Tape Sellotape FastMASK™

SKU: 1997319, 1996636, 1996633, 1996631, 1996880

DESCRIPTION

Sellotape® FastMASK™ is a flexible crepe paper masking tape, using a solvent-based natural rubber adhesive, designed for a wide range of masking applications. FastMASK™ has excellent conformability to irregular surfaces and is thin enough to avoid excessive paint build up on the edges.

FastMASK™ is designed for short term applications only and should be removed within 24 hours of application. Prolonged exposure to moisture can result in masking tape failing to remove cleanly.



APPLICATIONS

- General Purpose
- Bundling
- Temporary holding applications in industry
- Textured coatings applications
- Light duty packaging
- Splicing
- Labelling

SPECIFICATIONS

BACKING	Crepe Paper
ADHESIVE	Rubber
TOTAL THICKNESS	127 micron +/- 4
ADHESION TO STEEL	6.8 N per 25mm
TENSILE STRENGTH	4.6 kg/15mm
ELONGATION AT BREAK	10% +/- 4
TEMPERATURE RESISTANCE	+80

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification. Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Please refer to the Conditions of Sale for further information.

The conditions under which this product is stored affect its performance. Storage should be in dry, well ventilated rooms with a reasonably consistent temperature around 20°C and protected from continuous exposure to direct sunlight. The product should always be applied to clean, dry and grease free surfaces.