



# Scotch™ Splittable Flying Splice Tape

## Repulpable 9353R

### Product Data Sheet

September 2015

Supersedes: December 2014

#### Product Description

A double coated, splittable tape construction designed for straight line flying splices, furnished with repulpable acrylic adhesive on both sides and an easy release paper liner (also repulpable), with liner score for easy manual application.

#### Key Features

- Good shear for both cold set newsprint, and heat set commercial printing processes, and are specifically designed for improved adhesion to a wide range of coated papers
- A colour stabilized blue dye has been added to the splicing side adhesive to render the prepared splice pattern more visible after removing the liner just prior to splicing
- Modified splittable layer to provide to provide a lower overall splitting force for improved splice reliability on belt driven presses
- Can also be used on core driven presses.
- Modified reel side adhesive to increase holding power to a wide range of coated papers.

#### Physical Properties

<b>Adhesive Type Splicing side</b>	Blue Repulpable	
<b>Adhesive Type Reel side</b>	Clear Repulpable	
<b>Tape Colour</b>	Blue (splicing side) White (tabbing side)	
<b>Carrier</b>	White splittable non-siliconized tissue	
<b>Thickness (ASTM D-3652)</b> Tape without liner Liner Total	Before splitting 0.143 mm 0.056 mm 0.199 mm	After splitting Splice side 0.085 mm Reel side 0.059 mm
<b>Splittable Layer</b>	Cleavable layer, recessed 2 mm from leading tape edge	
<b>Release Liner</b>	Silicone coated semi-bleached kraft paper	

<b>Repulpability *</b>	Tape and Liner Completely *
<b>Bonding Strength</b>	Good affinity to Cellulose Fibres

\* is tested according to TAPPI UM 213, Procedure A. It is important to follow the weight and quantity measurement for fibre, splicing tape and water. Non-representative results can occur if test guidelines are not followed. The adhesives, carriers and liner are repulpable according to this test method.

<b>Applications</b>	<p>Designed for: Flying splice of paper webs in the printing industry</p> <p>Flying splice of paper webs in newsprint, offset litho, gravure and flexographic printing processes. The splittable layer has been modified to provide a lower overall splitting force for improved splice reliability on belt driven presses. This product can also be used on core driven presses</p>
<b>Storage</b>	<p>3M™ Splittable Flying Splice Tape Repulpable 9353R should be stored in the original carton at 18 - 25°C and 45 - 55 % Relative Humidity or refrigerated in the original carton for maximum shelf life.</p> <p>If the product is refrigerated, it should be allowed to warm to a temperature of at least 21°C before using.</p> <p>It is recommended that the protective liner be removed just prior to splicing, rather than leaving paper rolls with prepared splice patterns in storage without the protective liner.</p>
<b>Shelf Life</b>	12 months from date of manufacture by 3M when stored in the original carton.
<b>Precautionary Information</b>	<p>Refer to product label and Material Safety Data Sheet for health and safety information before using the product.</p> <p>For information please contact your local 3M Office.</p> <p><a href="http://www.3M.com">www.3M.com</a></p>
<b>For Additional Information</b>	<p>To request additional product information or to arrange for sales assistance, please call your local sales representative.</p> <p>Address correspondence to: 3M</p>
<b>Important Notice</b>	<p>All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law.</p>
<p>Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications.</p> <p>This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.</p>	

**3M Adrique Francophone**

Société à responsabilité limitée  
Au capital de 19.756.400 Dirhams  
Siège Social: ZF Ksar Almajaz Bureau  
6 Plateforme  
Lot n°2 Immeuble 4 zénith Tanger  
R.C : 74327, I.F. : 18745050

**3M Arabia, LLC**

Building 24-25 3M Saudi Arabia  
Zone C, Business Gate  
Airport Road Riyadh  
Saudi Arabia

**3M Egypt**

Finance Center, New Cairo  
Plot 140, Banking Sector  
5th settlement, Cairo  
Egypt

**3M Gulf Limited**

Dubai Internet City  
Building No. 11, 3rd Floor  
U.A.E

**3M Gulf Limited**

Ein El Mreisseh  
Saint Charles City Center, 4th Floor  
P.O.Box: 11-5025  
Riad el Solh  
Beirut 1107 2180  
Lebanon

**3M Gulf (Representation Office)**

Suhaim Bin Hamad St., Al Mana Towers  
Tower B, 2nd Floor, Office No.4  
Doha Qatar  
P.O.Box 14684

**3M Kenya Ltd.**

Victoria Towers, 3rd Floor  
Kilimanjaro Av, Upperhill  
Kenya

**3M Maroc**

Société à responsabilité limitée  
Au capital de 18.000.000 de Dirhams  
Siège Social: 33  
lot la colline II Sidi Maarouf – Casablanca  
R.C:78517, I.F.: 1084514  
Morocco

**3M Minnesota Mining &  
Manufacturing Nigeria Limited**

No 2 Sheraton Opebi Link Road  
Ikeja  
Lagos  
Nigeria

**3M Pakistan**

Islamic Chamber of Commerce Building  
ST-2/A, Block 9, KDA Scheme 5  
Clifton, Karachi  
Pakistan

**3M South Africa & Sub-Saharan  
Africa**

146A Kelvin Drive  
Woodmead, Sandton  
South Africa