



ExteriorMASK™

Woven PE Masking Tape

TECHNICAL DATA SHEET

Key Features



Tape colour provides clear visual identification.



30+ days clean removal with no stains/residue on most surfaces.



Extremely strong woven PE backing film with extra high tack premium acrylic adhesive.



Very good UV, weather and age resistance. Designed for use in extreme environments.



Ideal for most surface types without any adhesive leaching/shadowing effects.



Far better on the environment than PVC



Hand tearable.



Description

Sellotape®
ExteriorMASK™ is a woven PE backing film with extra high tack premium acrylic adhesive.

Ideal for most textured exterior surfaces, composite panels, plastic, aluminium and concrete. Produces a sharp-edged finish and no residue.

Tack Level: EXTRA HIGH



Available Widths:

18 & 24mm

SKU: 1985728, 1985729



MANUFACTURED IN
JAPAN

TECHNICAL INFORMATION

Backing	Woven PE
Adhesive	Premium Acrylic
Colour	Pink
Thickness	0.16 mm
Adhesion level	Extra high
Surface type	Rough to extreme texture
Adhesive Strength	3.84 N/10mm
Tensile Strength	36.9N/15mm
Elongation	6.6%
Temperature Resistance	+60°C
Shelf Life	12 months when stored in cartons at 23°C & 65% relative humidity
Solvent Resistance	Good
Age Resistance	Good
Core Size	76mm
Roll Length	30m
Roll Width	18 & 24mm



Applications

- Exterior fine line masking applications.
- Various sandblasting and marine masking applications.
- Provides sharp finish line masking on Elastomeric Paint and Membrane systems.
- Excellent for the application of masking film onto surfaces such as eaves and soffits for secure holding power with clean removal.
- Masking and protection during plastering / stucco application where a heavy duty exterior tape is required.
- Suitable for most surface types: concrete, tiles, composite panels, plastics, aluminium and metals.
- Prior surface testing is recommended to assess tape suitability to the surface and application.

The information supplied is accurate to the best of knowledge and is based upon current data. Properties quoted are typical and do not therefore, constitute a specification.

Customers are recommended to complete their own assessment of the product for its intended application under their own conditions. Please refer to the Conditions of Sale for further information.

The conditions under which this product is stored affect its performance. Storage should be in dry, well ventilated rooms with a reasonably consistent temperature around 20°C and protected from continuous exposure to direct sunlight. The product should always be applied to clean, dry and grease free surfaces.