

Sellotape® 1550 1552
55m PP Carton Closure Tapes
DATA SHEET



Product Description

- A tough bi-axially orientated polypropylene film with an aggressive adhesive. It is flexible and conforms well to irregular surfaces, and is release coated for ease of handling.
- Available in Clear (1550) and Brown (1552)

Applications

- Sealing parcels and general packaging applications
- Sealing tops and bottoms of cartons

Technical Performance

- | | |
|--|----------------|
| • Film: | Polypropylene |
| • Adhesive type: | Rubber |
| • Thickness of tape: | 55 microns |
| • Adhesion to steel: | 500-600 g/25mm |
| • Crossways tensile strength: | 20 kg/25mm |
| • Lengthways tensile strength: | 14 kg/25mm |
| • Elongation at break: | 150% |
| • Impact and abrasion resistance: | High |
| • Water resistance: | High |
| • Resistance to acids, alkalis and solvents: | High |
| • Service temperature: | -40°C to +70°C |

IMPORTANT – PLEASE READ

PRODUCT USE – All statements, technical information and recommendations contained in this document are provided for general information purposes only about the products referred to herein (Products). They are based upon tests or experience that Henkel New Zealand Limited (Henkel) believes are reliable. However, many factors beyond Henkel's control affect the use and performance of a Product in a particular application, including the conditions under which a Product is stored, handled and used and the time and environmental conditions in which a Product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is the user's responsibility to evaluate each Product to determine whether it is fit for a particular purpose and suitable for the user's method of application, as well as, to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of a Product. It is also the user's responsibility to check that the data sheet they have is the latest version that has been published by Henkel in connection with the Products.

NO WARRANTIES – In light of the foregoing, to the maximum extent permitted by law, Henkel MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE in connection with any Product. In addition, Henkel is not liable for representations made by suppliers or retailers about the Products.

LIMITATION OF REMEDIES AND LIABILITY – In any event (and without limiting the foregoing), THE EXCLUSIVE REMEDY, AT HENKEL'S SOLE DISCRETION, SHALL BE TO REFUND THE PURCHASE PRICE OF THE DEFECTIVE PRODUCT OR TO SUPPLY REPLACEMENT PRODUCT. Henkel shall not otherwise be liable for loss or damages, whether direct, indirect, special, or consequential, regardless of the legal theory asserted, including negligence.

Henkel Consumer Adhesives

2 Allens Road, East Tamaki, Auckland 2013

Phone: 0508 735 568

Website: www.sellotape.co.nz

