

Flatback Tape Scotch®

Data Sheet March/2004

Substitute: Initial

Product Description:

The # 3557 Flatback tape is constituted of a flat paper specially treated and coated with synthetic adhesive that provide an excellent performance to sealing box or others applications where a flatback tape is required. Not recommended for masking or in application where temperature resistance is required. This tape can be impress for flexo-system.

Product Characteristic:

Construction:

Backing: Flat paper specially treated

Adhesive: Synthetic rubber and resin (pressure sensitive)

Physical Properties:

<u>Note</u>: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes

(Test Method based on ASTM)

Adhesion to steel : 770 gf/12mm width (63 N/100mm width)

Tensile Strength : 8.0 kgf/12mm width (653 N/100mm width)

Total Thicness : 0.180 mm

Elongation at Break : 3.0 %

Holding Power to Fiberboard (shear) : + 5000 minutes

FEATURES	ADVANTAGES	BENEFITS
♦ Synthetic adhesive	♦ Instant adhesion	Reliable closure
	◆ Good adhesion in all kind fiberboard (recycled and virgin)	 Withstands normal shipping conditions
◆ Flat paper specially treated	◆ Good resistance and flexibility	◆ Good performance to sealing box

Applications:

- 1. Packaging boxes closure
- 2. Boxes and packs reinforcement
- 3. General packaging
- 4. Others applications where a flatback tape is requered

In add to the manual application, this tape can be applied with automatic and semi-automatic dispensers for sealing box.

Shelf Life:

To obtain best performance, use this product within two years from date of manufacture and store under conditions of 70 °F (21 °C) and 50% R.U. in the original carton.

Packaging System
3M do Brasil Ltda
Phone: 55 19 38387000

Via Anhanguera, Km 110

PO Box 123 Campinas - SP